

“New”



AIRTRONIC® D2/D4 air heater

Espar's new line of air heaters is called the *AIRTRONIC*. Applications include, bunk heat, small cargo and marine. The heaters cycle quietly through four heat levels to maintain comfort, without engine idling. These heaters have fewer parts and are lighter and smaller than their predecessor.

		AIRTRONIC D2	AIRTRONIC D4
Heat Output <i>BTU/hr (kW)</i>	Boost	7,500 (2.2)	13,600 (4)
	High	6,150 (1.8)	10,200 (3)
	Med	4,100 (1.2)	6,800 (2)
	Low	2,900 (0.8)	3,400 (1)
Fuel Consumption <i>US.gal/hr (l/hr)</i>	Diesel 1, 2 or kerosene		
	Boost	0.07 (0.28)	0.13 (0.51)
	High	0.06 (0.23)	0.10 (0.38)
	Med	0.04 (0.14)	0.07 (0.25)
Electrical (12v) Consumption	Boost	2.8 amps	3.3 amps
	High	1.9 amps	2.0 amps
	Med	1.0 amps	1.1 amps
	Low	0.67 amps	0.6 amps
Air throughput <i>cfm</i>	Boost	48	85
	High	40	69
	Med	27	50
	Low	19	30
Weight		6 lbs. (2.7 kg)	9.9 lbs. (4.5 kg)

